


Ziligen© Data Sheet

Name	NP GG 14/5		
Stock Number	-	Update Date	Feb 18, 2019, 6:50:19 AM

Material Structure			
Total Thickness	5.00	+/- 0.20	
Carcass Material	Polyamide		
Carcass Material Thickness	0.80		
Weight	5.80		
Working Temperature	-20 °C	80 °C	

Top Cover		Bottom Cover	
Material	NBR	Material	NBR
Color	Green	Color	Green
Thickness	2.10 mm	Thickness	2.10 mm
Thickness Tolerance	0.10 mm	Thickness Tolerance	0.10 mm
Pattern	GSTR	Pattern	GSTR
Hardness	60 sHa	Hardness	60 sHa
Electrostatic Properties	Antistatic		

Tension Member		Maximum Production Width	
Breaking Load	315 N/mm		500 mm
Working Load %1 Elongation	14 N/mm		
		Drum Diameter	50 mm

Splicing			
Type of Splice	Overlap	Press Pressure	0
Press Temperature	120	Pressing Time	35
Rubber(Leather) Adhesive	AF	Polyamide Adhesive	K-80
Press Application	-		

General Information	
Product Group	Power Transmission Belt
Market Segment	It is used for folder gluer machines

Create Date: Dec 12, 2019, 1:15:35 PM GMT

Create PDF