


Ziligen© Data Sheet

Name	NP GG 20		
Stock Number	-	Update Date	Sep 30, 2018, 9:00:00 PM

Material Structure			
Total Thickness	2.40	+/- 0.20	
Carcass Material	Polyamide		
Carcass Material Thickness	1.00		
Weight	2.85		
Working Temperature	80 °C	-20 °C	

Top Cover		Bottom Cover	
Material	XNBR	Material	XNBR
Color	Green	Color	Green
Thickness	0.70 mm	Thickness	0.70 mm
Thickness Tolerance	0.10 mm	Thickness Tolerance	0.10 mm
Pattern	GSTR	Pattern	GSTR
Hardness	70 sHa	Hardness	70 sHa
Electrostatic Properties	Antistatic		

Tension Member		Maximum Production Width	
Breaking Load	450 N/mm	Maximum Production Width	500 mm
Working Load %1 Elongation	20 N/mm	Drum Diameter	70 mm

Splicing			
Type of Splice	Overlap	Press Pressure	0
Press Temperature	110	Pressing Time	20
Rubber(Leather) Adhesive	AF	Polyamide Adhesive	K-80
Press Application	-		

General Information	
Product Group	Power Transmission Belt
Market Segment	-

Create Date: Dec 11, 2019, 2:12:51 PM GMT

Create PDF