


## Ziligen© Data Sheet

<b>Name</b>	LL 10		
<b>Stock Number</b>	-	<b>Update Date</b>	Aug 20, 2020, 10:09:03 AM

Material Structure			
<b>Total Thickness</b>	4.50	+/- 0.20	
<b>Carcass Material</b>	Polyamide		
<b>Carcass Material Thickness</b>	0.50		
<b>Weight</b>	4.95		
<b>Working Temperature</b>	80 °C	-20 °C	

Top Cover		Bottom Cover	
<b>Material</b>	Leather	<b>Material</b>	Leather
<b>Color</b>	Grey	<b>Color</b>	Grey
<b>Thickness</b>	2.00 mm	<b>Thickness</b>	2.00 mm
<b>Thickness Tolerance</b>	0.10 mm	<b>Thickness Tolerance</b>	0.10 mm
<b>Pattern</b>	-	<b>Pattern</b>	-
<b>Hardness</b>	0 sHa	<b>Hardness</b>	0 sHa
<b>Electrostatic Properties</b>	Antistatic		

Tension Member		Maximum Production Width	
<b>Breaking Load</b>	225 N/mm		500 mm
<b>Working Load %1 Elongation</b>	10 N/mm	Drum Diameter	
			40 mm

Splicing			
<b>Type of Splice</b>	Overlap	<b>Press Pressure</b>	0
<b>Press Temperature</b>	110	<b>Pressing Time</b>	15
<b>Rubber(Leather) Adhesive</b>	PU	<b>Polyamide Adhesive</b>	K-80
<b>Press Application</b>			

General Information	
<b>Product Group</b>	Power Transmission Belt
<b>Market Segment</b>	-

Create Date: Mar 31, 2021, 6:52:10 AM GMT

Create PDF