


## Ziligen© Data Sheet

<b>Name</b>	LL 30			
<b>Stock Number</b>	-	<b>Update Date</b>	Sep 1, 2020, 12:24:47 PM	
<b>Material Structure</b>				
<b>Total Thickness</b>	5.60	+/- 0.20		
<b>Carcass Material</b>	Polyamide			
<b>Carcass Material Thickness</b>	1.50			
<b>Weight</b>	6.05			
<b>Working Temperature</b>	80 °C	-20 °C		
<b>Top Cover</b>		<b>Bottom Cover</b>		
<b>Material</b>	Leather		<b>Material</b>	Leather
<b>Color</b>	Grey		<b>Color</b>	Grey
<b>Thickness</b>	2.00 mm		<b>Thickness</b>	2.00 mm
<b>Thickness Tolerance</b>	0.10 mm		<b>Thickness Tolerance</b>	0.10 mm
<b>Pattern</b>	-		<b>Pattern</b>	-
<b>Hardness</b>	0 sHa		<b>Hardness</b>	0 sHa
<b>Electrostatic Properties</b>	Antistatic			
<b>Tension Member</b>		<b>Maximum Production Width</b>		
<b>Breaking Load</b>	675 N/mm		520 mm	
<b>Working Load %1 Elongation</b>	30 N/mm		<b>Drum Diameter</b>	200 mm
<b>Splicing</b>				
<b>Type of Splice</b>	Overlap		<b>Press Pressure</b>	0
<b>Press Temperature</b>	110		<b>Pressing Time</b>	30
<b>Rubber(Leather) Adhesive</b>	PU		<b>Polyamide Adhesive</b>	K-80
<b>Press Application</b>				
<b>General Information</b>				
<b>Product Group</b>	Power Transmission Belt			
<b>Market Segment</b>	-			

Create Date: Mar 31, 2021, 6:53:52 AM GMT

Create PDF