



ziligen

**DATA SHEET
LT 54**

| | |
|--------------|------------|
| File Nr. | FR.LTİ.10 |
| Revision Nr. | 0 |
| Date | 03.05.2011 |
| Page Nr. | 1 |

DESIGN

Top Surface

Material

Nylon fabric

Colour

Black

Thickness

0,3 mm +/- 0,05 mm

Pattern

-

Drive Surface

Material

Leather

Colour

Grey

Thickness

2,0 mm +/- 0,1 mm

Pattern

-

Carcass material / thickness

Polyamid / 2,75 mm

Working load at 1 % elongation

54 N / mm

Breaking Load

1215 N / mm

Elegnation at break

% 22

Total thickness

5,05 mm +/- 0,15 mm

Weight

5,55 Kg / m²

Min. pulley diameter

380 mm.

Working Temp. (min.-max.)

-20 + 80° C

Max. production width

520 mm

Electrostatic properties

Antistatic

Storage conditions:

25 °C at room temperature and
60 % relative humidity.

Failure to comply with these
requirements, the product
can change the size and shape.

Type of splice

Overlap

Press temperature

110 °C

Pressing time

35 min.

Leather adhesive

PU

Polyamide & nylon adhesive

K-80

Splice parameter Table Nr.

YTK-20

