



**ziligen**

**DATA SHEET  
NP GT 10**

|              |            |
|--------------|------------|
| File Nr.     | FR.GTİ.02  |
| Revision Nr. | 0          |
| Date         | 03.05.2011 |
| Page Nr.     | 1          |

**DESIGN**

**Top Surface**

Material

Nylon fabric

Colour

Black

Thickness

0,3 mm +/- 0,05 mm

Pattern

-

**Drive Surface**

Material

XNBR Rubber

Colour

Green

Thickness

0,7 mm +/- 0,1 mm

Pattern

GSTR

Carcass material / thickness

Polyamid / 0,5 mm

Working load at 1 % elongation

10 N / mm

Breaking Load

225 N / mm

Elegnation at break

% 22

Total thickness

1,5 mm +/- 0,15 mm

Weight

1,62 Kg / m<sup>2</sup>

Min. pulley diameter

30 mm.

Working Temp. (min.-max.)

-20 + 80° C

Max. production width

520 mm

Electrostatic properties

Antistatic

**Storage conditions:**

25 °C at room temperature and  
60 % relative humidity.

Failure to comply with these  
requirements, the product  
can change the size and shape.

Type of splice

Overlap

Press temperature

110 °C

Pressing time

15 min.

Rubber adhesive

AF

Polyamide & nylon adhesive

K-80

Splice parameter Table Nr.

YTK-20

